

### Affected Powermax65 part numbers

Item Number	Item Description
083234	Powermax65 power supply, 200-600V 1/3-PH, CSA
083266	Powermax65 power supply, 200-600V 1/3-PH, CSA, plus CPC port
083267	Powermax65 power supply, 200-600V 1/3-PH, CSA, plus CPC & Serial ports
083235	Powermax65 power supply, 400V 3-PH, CE
083268	Powermax65 power supply, 400V 3-PH, CE, plus CPC port
083269	Powermax65 power supply, 400V 3-PH, CE, plus CPC & Serial ports
083307	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 15° handheld torches w/consumables, 7.6m (25') leads
083308	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 15° handheld torches w/consumables, 15.2m (50') leads
083275	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° handheld torch w/consumables, 7.6m (25') lead
083276	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° handheld torch w/consumables, 15.2m (50') lead
083270	Powermax65 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 7.6m (25') lead
083271	Powermax65 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 15.2m (50') lead
083273	Powermax65 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 7.6m (25') lead, filter w/guard
083300	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 180° torches w/consumables, 7.6m (25') lead, remote
083277	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead, remote
083278	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 15.2m (50') lead, remote
083294	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead
083302	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 15.2m (50') lead
083328	Powermax65 system, 200-600V, 1/3-PH, CSA, plus CPC & Serial Ports, 180° torch w/consumables, 7.6 (25') lead w/hnd clp
083303	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC & Serial ports, 180° torch w/consumables, 7.6m (25') lead w/ring
083305	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC & Serial ports, 180° torch w/consumables, 15.2m (50') lead w/ring
083309	Powermax65 system, 400V 3-PH, CE, plus CPC port, 75° & 15° handheld torches w/consumables, 7.6m (25') leads
083310	Powermax65 system, 400V 3-PH, CE, plus CPC port, 75° & 15° handheld torches w/consumables, 15.2m (50') leads
083284	Powermax65 system, 400V 3-PH, CE, plus CPC port, 75° handheld torch w/consumables, 7.6m (25') lead
083285	Powermax65 system, 400V 3-PH, CE, plus CPC port, 75° handheld torch w/consumables, 15.2m (50') lead
083279	Powermax65 system, 400V 3-PH, CE, 75° handheld torch w/consumables, 7.6m (25') lead
083280	Powermax65 system, 400V 3-PH, CE, 75° handheld torch w/consumables, 15.2m (50') lead
083282	Powermax65 system, 400V 3-PH, CE, 75° handheld torch w/consumables, 7.6m (25') lead, filter w/guard
083301	Powermax65 system, 400V 3-PH, CE, plus CPC port, 75° & 180° torches w/consumables, 7.6m (25') lead, remote
083286	Powermax65 system, 400V 3-PH, CE, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead, remote
083287	Powermax65 system, 400V 3-PH, CE, plus CPC port, 180° machine w/consumables, 15.2m (50') lead, remote
083293	Powermax65 system, 400V 3-PH, CE, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead
083304	Powermax65 system, 400V 3-PH, CE, plus CPC & Serial ports, 180° machine torch w/consumables, 7.6m (25') lead w/ring
083306	Powermax65 system, 400V 3-PH, CE, plus CPC & Serial ports, 180° machine torch w/consumables, 15.2m (50') lead w/ring
083288	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° torch w/consumables, 7.6m (25') lead, En training kit
083290	Powermax65 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° torch w/consumables, 7.6m (25') lead, Fr training kit
083326	Powermax65 system, 400V 3-PH, CE, plus CPC & Serial ports, 180° machine torch w/consumables, 10.7m (35') lead