**Hypertherm**®

Hypertherm Europe B.V.
Vaartveld 9, 4704 SE
Roosendaal
The Netherlands
www.hypertherm.com

## Affected Powermax85 part numbers

| Item Number | Item Description |
|---|---|
| 087068 | Powermax85 power supply, 400V 3-PH, CE |
| 087106 | Powermax85 power supply, 400V 3-PH, CE, plus CPC port |
| 087107 | Powermax85 power supply, 400V 3-PH, CE, plus CPC & Serial ports |
| 087067 | Powermax85 power supply, 200-600V 1/3-PH, CSA |
| 087104 | Powermax85 power supply, 200-600V 1/3-PH, CSA, plus CPC port |
| 087105 | Powermax85 power supply, 200-600V 1/3-PH, CSA, plus CPC & Serial ports |
| 087144 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 15° handheld torches w/consumables, 7.6m (25') leads |
| 087145 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 15° handheld torches w/consumables, 15.2m (50') leads |
| 087113 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° handheld torch w/consumables, 7.6m (25') lead |
| 087114 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° handheld torch w/consumables, 15.2m (50') lead |
| 087108 | Powermax85 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 7.6m (25') lead |
| 087109 | Powermax85 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 15.2m (50') lead |
| 087111 | Powermax85 system, 200-600V 1/3-PH, CSA, plus 75° handheld torch w/consumables, 7.6m (25') lead, filter w/guard |
| 087135 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° & 180° torches w/consumables, 7.6m (25') lead, remote |
| 087115 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead, remote |
| 087116 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 15.2m (50') lead, remote |
| 087132 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead |
| 087137 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 180° machine torch w/consumables, 15.2m (50') lead |
| 087164 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC  & Serial ports, 180° torch w/consumables, 7.6 m (25') lead w/hnd clp |
| 087138 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC & Serial ports, 180° torch w/consumables, 7.6m (25') lead w/ring |
| 087140 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC & Serial ports, 180° torch w/consumables, 15.2m (50') lead w/ring |
| 087146 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° & 15° handheld torches w/consumables, 7.6m (25') leads |
| 087147 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° & 15° handheld torches w/consumables, 15.2m (50') leads |
| 087122 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° handheld torch w/consumables, 7.6m (25') lead |
| 087123 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° handheld torch w/consumables, 15.2m (50') lead |
| 087117 | Powermax85 system, 400V 3-PH, CE, plus 75° handheld torch w/consumables, 7.6m (25') lead |
| 087118 | Powermax85 system, 400V 3-PH, CE, plus 75° handheld torch w/consumables, 15.2m (50') lead |
| 087120 | Powermax85 system, 400V 3-PH, CE, plus 75° handheld torch w/consumables, 7.6m (25') lead, filter w/guard |
| 087136 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° & 180° torches w/consumables, 7.6m (25') lead, remote |
| 087124 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead, remote |
| 087125 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 180° machine torch w/consumables, 15.2m (50') lead, remote |
| 087131 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 180° machine torch w/consumables, 7.6m (25') lead |
| 087139 | Powermax85 system, 400V 3-PH, CE, plus CPC & Serial ports, 180° machine torch w/consumables, 7.6m (25') lead w/ring |
| 087141 | Powermax85 system, 400V 3-PH, CE, plus CPC & Serial ports, 180° machine torch w/consumables, 15.2m (50') lead w/ring |
| 087126 | Powermax85 system, 200-600V 1/3-PH, CSA, plus CPC port, 75° torch w/consumables, 7.6m (25') lead, En training kit |
| 087127 | Powermax85 system, 400V 3-PH, CE, plus CPC port, 75° handheld torch w/consumables, 7.6m (25') lead & En training kit |