

Powermax85 SYNC

The following 200-600V, 1/3 PH, 50/60Hz, CSA, Auto-Voltage/Phase systems are impacted.

Hand Systems	
087183	75-degree handheld torch, 7.6m (25') lead
087184	75-degree handheld torch, 15.2m (50') lead
087185	CPC port, 75-degree handheld torch, 7.6m (25') lead
087186	CPC port, 75-degree handheld torch, 15.2m (50') lead
087191	CPC port, 75-degree 7.6m (25') hand torch, 10.7m (35') machine torch, 7.6m (25') remote
087187	75-degree handheld torch, 15-degree hand torch, 7.6m (25') lead
Machine Systems	
087189	CPC port, 180-degree machine torch, 7.6m (25') lead
087190	CPC port, 180-degree machine torch, 15.2m (50') lead
087192	CPC, and Serial Ports, 180-degree torch, 7.6 (25') lead
087207	CPC port, 180-degree machine torch, 7.6m (25') lead, remote
087208	CPC port, 180-degree machine torch, 15.2m (50') lead, remote
087218	CPC and Serial ports, 180-degree torch, 10.7m (35') lead
087219	CPC and Serial ports, 180-degree torch, 15.2m (50') lead
Power Supplies	
087213	200-600V 1/3 PH, CSA
087214	200-600V 1/3 PH, CSA, plus CPC port
087215	200-600V 1/3 PH, CSA, plus CPC and Serial ports

400V, 3 PH, 50/60Hz, CE/CCC hand and mechanized systems are not impacted.



Hypertherm, Inc.
P.O. Box 5010
21 Great Hollow Road
Hanover, NH 03755 USA
www.hypertherm.com

Powermax105 SYNC

The following 200-600V, 3 PH, 50/60Hz, CSA, Auto-Voltage/Phase systems are impacted.

Hand Systems	
059625	75-degree handheld torch, 7.6m (25') lead
059626	75-degree handheld torch, 15.2m (50') lead
059627	CPC port, 75-degree handheld torch, 7.6m (25') lead
059628	CPC port, 75-degree handheld torch, 15.2m (50') lead
059634	CPC port, 75-degree handheld torch, 15-degree hand torch, 7.6 m (25') lead
Machine Systems	
059636	CPC port, 180-degree machine torch, 7.6m (25') lead, remote
059639	CPC port, 180-degree machine torch, 15.2 m (50') lead, remote
059637	CPC port, 180-degree machine torch, 7.6m (25') lead
059638	CPC port, 180-degree machine torch, 15.2 m (50') lead
059684	CPC and Serial ports, 180-degree torch, 7.6m (25') lead
059687	CPC port, 180-degree machine torch, 10.7m (35') lead, 7.6m (25') hand torch
059762	CPC and Serial ports, 180-degree torch, 10.7m (35') lead
059763	CPC and Serial ports, 180-degree torch, 15.2m (50') lead
Power Supplies	
059704	200-600V 3-PH, CSA
059705	200-600V 3-PH, CSA, plus CPC port
059706	200-600V 3-PH, CSA, plus CPC and serial ports

The following 230-400V, 3 PH, 50/60Hz, CE, Auto-Voltage systems are impacted.

Hand Systems	
059679	75-degree handheld torch, 7.6m (25') lead
059680	75-degree handheld torch, 15.2m (50') lead
Machine Systems	
059682	CPC port, 180-degree machine torch, 7.6m (25') lead
059683	CPC port, 180-degree machine torch, 15.2m (50') lead
059712	CPC and Serial ports, 180-degree machine torch, 7.6m (25') lead
059764	CPC and Serial ports, 180-degree machine torch, 10.7m (35') lead
Power Supplies	
059701	230-400V 3-PH, CE
059702	230-400V 3-PH, CE, plus CPC port
059703	230-400V 3-PH, CE, plus CPC and serial ports

380-400V, 3 PH, 50/60Hz, CE/CCC, Fixed Voltage systems are not impacted.